

ARCHITECTURAL COLOR CHART

❖ SIGNATURE® 300 Standard Colors

KYNAR 500®
HYLAR 5000®
LOW GLOSS

- Final color selection should be made from actual color chips.
- For the most current information available, visit our website at www.mbc.com.
- See product catalog for gauge and color availability.
- All products available in smooth or embossed finish.
- Heavier gauges, narrower widths, striations and embossing minimize "oil canning."
- All Signature® 300 and 300 Metallic are low gloss colors.
- A 25-year limited paint warranty is available for all colors upon written request. For locations outside the continental USA and Canada, please inquire.
- Signature® is a registered trademark of NCI Group, Inc. KYNAR 500® is a registered trademark of Arkema, Inc. HYLAR 5000® is a registered trademark of Solvay Solexis.



HARBOR BLUE ★
SR .28 SRI 30




COLONIAL RED ★
SR .34 SRI 37



MEDIUM BRONZE ★
SR .33 SRI 36




PACIFIC BLUE ★
SR .29 SRI 31



SNOW WHITE ★
SR .65 SRI 79



SLATE GRAY ★
SR .37 SRI 41



ALMOND ★
SR .63 SRI 76



MIDNIGHT BRONZE ★
SR .29 SRI 31



EVERGLADE ★
SR .33 SRI 36



BROWNSTONE ★
SR .47 SRI 54



TUNDRA ★
SR .46 SRI 53



SPRUCE ★
SR .36 SRI 40



BRITE RED
SR .49 SRI 55



HUNTER GREEN ★
SR .35 SRI 39



CLASSIC GREEN ★
SR .28 SRI 30



NATURAL PATINA ★
SR .41 SRI 47

❖ SIGNATURE® 300 Metallic

KYNAR 500®
HYLAR 5000®
LOW GLOSS



COPPER METALLIC ★
SR .45 SRI 51



SILVER METALLIC ★
SR .52 SRI 60

Note: Metallic coatings are directional. Panels and trim must be installed oriented in the same direction to prevent perceived shade variances. Directional arrows are on the back side of panels and trim to aid in the proper orientation.

❖ SIGNATURE® 200 Standard Colors

SILICONIZED
POLYESTER

Polar White is a Straiht Polyester.



BURNISHED SLATE ★
SR .28 SRI 29



POLAR WHITE ★
SR .58 SRI 69



CHARCOAL GRAY ★
SR .28 SRI 30



LIGHT STONE ★
SR .50 SRI 58



RUSTIC RED ★
SR .36 SRI 40



KOKO BROWN ★
SR .28 SRI 30



FERN GREEN ★
SR .28 SRI 29



COAL BLACK ★
SR .30 SRI 31



HAWAIIAN BLUE ★
SR .32 SRI 35

★ ENERGY STAR
Qualified Color



Houston, TX 877-713-6224
Adel, GA 888-446-6224
Atlanta, GA 877-512-6224
Atwater, CA 800-829-9324


Dallas, TX 800-653-6224
Indianapolis, IN 800-735-6224
Jackson, MS 800-622-4136
Lubbock, TX 800-758-6224

Memphis, TN 800-206-6224
Oklahoma City, OK 800-597-6224
Omaha, NE 800-458-6224
Phoenix, AZ 888-533-6224


Richmond, VA 800-729-6224
Rome, NY 800-559-6224
Salt Lake City, UT 800-874-2404
San Antonio, TX 800-598-6224

ARCHITECTURAL PANEL PROFILES

DESIGNER® SERIES




16.0 Fluted




12.0 Flat


SHADOWRIB™




NUWALL®




WALL / LINER PANELS



FW 120-1 (with Bead)




ILM-240-3 (with Beads)




ILM-240-2 (with Beads)

ARTISAN® SERIES




L-12



L-12 (with Beads)


8" and 10" also available

CLASSIC® SERIES




16" also available

QWIKLOK™




FLEXLOC®




8 1/2" and 9 1/2" also available


CRAFTSMAN™ SERIES



SB-12



LB-12




HB-12

16 1/2" also available


Standing Seam Vertical Leg

LOKSEAM®




Snap-Together System
12" and 16" also available

BATTENLOK® HS




Field Seamed System
12" also available

SUPERLOK®



Field Seamed System
12" also available


CURVED BATTENLOK®



Field Seamed System


Trapezoidal Leg

ULTRA-DEK®



Snap-Together System
12" and 18" also available

DOUBLE-LOK®



Field Seamed System
12" and 18" also available

What is

Solar Reflectivity (SR)?

Solar reflectivity or reflectance (SR) is the ability of a material to reflect solar energy from its surface back into the atmosphere. The SR value is a number from 0 to 1.0. A value of 0 indicates that the material absorbs all solar energy and a value of 1.0 indicates it is all reflected. ENERGY STAR requires SR testing of both new and aged roof products. New products must have an SR value of 0.25 or higher for steep slope (above 2:12) roofing and an SR value of 0.65 or higher for low slope (2:12 or less) roofing. Aged testing takes 3 years to complete, so not all products that meet the initial requirements are qualified. For more information, please go to www.energystar.gov.

What is

Solar Reflectance Index (SRI)?

The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. Emissivity is a material's ability to release absorbed energy. To meet LEED requirements, a roofing material must have an SRI of 29 or higher for steep slope (above 2:12) roofing and an SRI value of 78 or higher for low slope (2:12 or less) roofing. For more information, please go to www.usgbc.org.

SIGNATURE® 300 - KYNAR 500®/HYLAR 5000®

	SR #	SRI #
HARBOR BLUE	.28	30
COLONIAL RED	.34	37
MEDIUM BRONZE	.33	36
PACIFIC BLUE	.29	31
HUNTER GREEN	.35	39
SNOW WHITE	.65	79
SLATE GRAY	.37	41
ALMOND	.63	76
MIDNIGHT BRONZE	.29	31
CLASSIC GREEN	.28	30
EVERGLADE	.33	36
BROWNSTONE	.47	54
TUNDRA	.46	53
SPRUCE	.36	40
NATURAL PATINA	.41	47
BRITE RED	.49	55

SIGNATURE® 300 METALLIC - KYNAR 500®/HYLAR 5000®

	SR #	SRI #
COPPER METALLIC	.45	51
SILVER METALLIC	.52	60

SIGNATURE® 200 - SILICONIZED POLYESTER

	SR #	SRI #
BURNISHED SLATE	.28	29
POLAR WHITE	.58	69
CHARCOAL GRAY	.28	30
LIGHT STONE	.50	58
HAWAIIAN BLUE	.32	35
RUSTIC RED	.36	40
KOKO BROWN	.28	30
FERN GREEN	.28	29
COAL BLACK	.30	31